Stichting Theaters Tilburg **Technical Specifications** Schouwburg



General Information

Adress

City **Tilburg**

Theater Schouwburg Concertzaal Tilburg

Hall Schouwburg

Visiting Address & Parking Louis Bouwmeesterplein 1

Performers entrance 5038 TN Tilburg

Location Performers entrance

Loading Dock

Lift 1 Louis Bouwmeesterplein, Tilburg

Location Trailerlift 1

Lift 2 Kloosterstraat 6-2, Tilburg

Location Trailerlift 2

Phone numbers

General 013 5490 390 Ticket service 013 5432 220

Contact information

Contact Technical department Bas van Steen 013 5490 341

> **Ineke Padmos** 013 5490 327 techniek@schouwburgconcertzaaltilburg.nl

Contact Production 013 5490 316 Anne Rosenau

arosenau@schouwburgconcertzaaltilburg.nl

Standard times

Lunch 12:30 - 13:00Dinner 17:00 - 19:00

Evening showtime 20:15 Showtime matinee variable

Fire alarms can be turned off, but always in consultation with the technicians of Schouwburg Concertzaal Tilburg

Accessibility

The main entrances of the Schouwburg, Concertzaal and Studio are located on the Schouwburgring. The coordinating address and the backstage entrance is Louis Bouwmeesterplein 1, 5038 TN Tilburg.

Parking

The municipality of Tilburg does not provide free parking around the theatre. There are multiple paid car parks around Schouwburg Concertzaal Tilburg. Parking can be paid with cash or by debit- or credit card.

Please take into account that Thursday evenings are extra busy due to extended opening hours of stores in the city centre. Parking takes considerably more time than on other days. Extra crowds can also be expected on Sundays and holidays.

Public transport

Tilburg Central station is located 15 minutes from the theatre. It also an option to take a city taxi or a bus.

Loading dock

To be able to load and unload trucks, two lifts are used to lift trucks up to stage level.

Max. length trucks: 18m

At its smallest, the passage to the stage is 3m wide and 6m high

Location lift 1

Location lift 2



Technical general information

Venue capacity

| i diriare carporately | |
|----------------------------------|------------------------|
| Total | 860 |
| Floor level, incl. orchestra pit | 544 |
| orchestra pit | 39 |
| 1 ^e Balcony | 169 |
| 2 ^e Balcony | 164 |
| Standard amount of FOH | 16 (2x8) Other numbers |
| places | in consultation |

Soft furnishings and details

| | · · · | |
|---------------|------------------|--------------------|
| Stage floor | Material | Keroewing Hardwood |
| | Thickness | 28mm - 500 kg/m2 |
| | | |
| Marley | Colour | black |
| | Width | 1.60m per lane |
| | | |
| House curtain | Colour | Red/green |
| | Operation | Stage Left, manual |
| | Way of Opening | Traveler |
| | | |

Soft goods and masking

| | General | Colour | Ni | ght Blue |
|-----------------------|-----------|--------|-------|----------|
| | | | | |
| 12x | leg | Height | 10.00 | meter |
| | | Width | 05.50 | meter |
| | | | | |
| 5x | border | Height | 04.00 | meter |
| | | Width | 21.00 | meter |
| | | | | |
| 1x | border | Height | 06.00 | meter |
| | | Width | 21.00 | meter |
| | | | | |
| 3x f | ull black | Height | 10.00 | meter |
| Consists out of 12 ex | xtra legs | Width | 20.00 | meter |
| | | | | |
| 2x sid | e blacks | Height | 09.00 | meter |
| Consists out of 6 sh | hort legs | Width | 13.50 | meter |
| | | | | |
| 2x sid | e blacks | Height | 09.00 | meter |
| Consists out of 4 pie | ces on a | Width | 02.00 | meter |
| rails, attached pern | nanently | | | |
| | | | | |
| Су | clorama | Height | 10.00 | meter |
| | | Width | 21.00 | meter |
| | | | | |
| Blac | ck gauze | Height | 09.00 | meter |
| | | Width | 16.00 | meter |
| | | | | |
| O _l | pera foil | Height | 08.00 | meter |
| | | Width | 16.00 | meter |



Dimensions

Stage dimensions

| Proscenium | Height | | 08.70 | meter |
|--------------------------------|--------|------|-------|-------|
| | Width | | 13.70 | meter |
| | | | | |
| Portal | Height | Min. | 00.00 | meter |
| | | Max. | 08.15 | meter |
| | Width | Min. | 10.00 | meter |
| | | Max. | 15.80 | meter |
| | | | | |
| Stage floor | Width | | 21.00 | meter |
| Including wing space | | | 34.00 | meter |
| | | | | |
| Zero to rear wall | Depth | | 12.00 | meter |
| Edge of the apron to rear wall | Depth | | 15.00 | meter |
| Edge of the orchestra pit to | Depth | | 18.00 | meter |
| rear wall | | | | |

Distances from zero

| Edge of the apron | -03.00 | meter |
|-------------------------|--------|-------|
| Rear wall | 14.70 | meter |
| Backwall auditorium | -19.60 | meter |
| House curtain | -01.51 | meter |
| Proscenium fly bar | -01.26 | meter |
| Portal | -0.79 | meter |
| Backside safety curtain | -1.78 | meter |

Heights relative to stage floor

| _ | | | | |
|-------|-------------------|------|-------|-------|
| | Fly loft | | 20.70 | meter |
| Maxim | um fly bar height | | 19.70 | meter |
| | Side bridges | Min. | 1.00 | meter |
| | | Max. | 12.00 | meter |





Orchestra pit

The orchestra pit is variable in height between the orchestra pit level and the stage. The pit exists out of a fixed room beneath the stage and a moving part in the auditorium

The orchestra pit is accessible via 2 doors, left and right through normal sized doors and a small set of stairs. Instruments can be brought to the orchestra pit from ground level and stage level. For the dimensions of the orchestra pit, see the floorplan on the website.

A conductor camera is available.

Orchestra facilities

| Conductor riser | 1x | 100 x 100 cm, variable height, including conductor stand |
|------------------|-----|--|
| | | |
| Orchestra chairs | 55x | Without armrests |
| | | |
| Music stands | 45x | Adjustable height |
| | | |
| Reading lights | 45x | For music stands |





The fly system is computer controlled with a TNM system by the manufacturer Trekwerk. All flybars except the flybars in the auditorium and 2 flybars underneath the side bridges are connected to this system. The loading capacity of the system is assessed according to the NPR8020-10 with a safety factor of 10 (hoists above persons)

The SWL/WLL on all lifting materials must therefore be halved. All hoisting equipment of Schouwburg Concertzaal Tilburg is rated with a factor 10. Rigging and hanging of loads is only permitted with certified equipment. Such is all at the discretion of the on duty fly bar operator of Schouwburg Concertzaal Tilburg.

The fly system can only be controlled by a qualified operator from Schouwburg Concertzaal Tilburg.


Fly bars

59 fly bars

Max. Height 19.70 meter
Min. Height 00.05 meter
Fly bar length 21.00 meter
Max. Speed 1.7 m/s

Distance between fly bars 20 cm (with the exception of fly bars 02, 20, 38, 56, due to steel beams 30-35 cm distance)

Distance between zero to 1st fly bar is 00.38 meter.



Max. load, see below.

| | Α | В | С | D | E |
|----------------|--------|--------|-------|-------|-------|
| Fly bars | 500 kg | 250 kg | 250kg | 300Kg | 75 kg |
| Proscenium fly | 500 kg | 250 kg | 250kg | 300Kg | 75 kg |
| bar | | | | | |
| Side fly bars | 500 kg | 250 kg | 250kg | 300Kg | 75 kg |

Side fly bars

6 side fly bars;

2 on the inside of the side bridges, fly bar length 12.50m;

2 on the outside of the side bridges, fly bar length 11.50m; max. load see table above

2 side bars underneath side bridges, not controlled by the fly system. Max. load is 300 kg



Proscenium fly bar

Flybar length 19.00 meter Max. speed 1.7 m/s Distance to zero -01.26 meter

Max. load see table above



The auditorium flybars are mainly used for audio rigging. 1 left , fly bar length 2m, max load 500 kg 1 centre, fly bar length 2m , max load 300 kg 1 right, fly bar length 2m , max load 500 kg

There is also 1 fly bar located underneath the first FOH bridge. Max. load is 300kg with equal load, 150kg point load.

Point hoists

12 point hoists (chain hoists)

4 areas which can all contain a maximum of 3 hoists.

Max. load is 500kg Max. height is 20m Min. height 0m



Electrics and infrastructure

Power distribution

All high voltage current connections have CEE-norm red connectors, with 3 phases, zero and ground

| 125A | 1x | Stage left, downstage |
|----------|----|---------------------------------------|
| | 1x | Stage right, downstage |
| | 1x | Stage right, centre stage |
| | | |
| 63A | 2x | Stage right, centre stage |
| | | |
| 32A | 2x | Stage right, centre stage |
| | 1x | Stage right, down stage (audio) |
| | 1x | Stage left, centre stage (16 A fuse) |
| | 1x | Stage left, downstage (audio) |
| | | |
| | 1x | Side bridge stage right |
| | 1x | Side bridge stage left |
| | | |
| 220V 16A | | Multiple points, CEE and wall sockets |
| | | SUCKELS |

DMX

The DMX- network is installed as a star-network, of which the middle is located at stage left, downstage. DMX can be sent and received at multiple locations throughout the venue.

Network

The venue also has an extensive CAT7 network. Multiple lines for audio, video and sACN are located throughout the venue.

LED conversion

The LED fixtures in the 2nd FOH and in the proscenium can be controlled with one channel. For the Cyclorama 4 colours are available. Each light can be programmed with any colour desired by the visiting company.

If desired, It is also possible to control the LED fixtures in their full mode with sACN. For a current patch list, contact our technical department at techniek@schouwburgconcertzaaltilburg.nl



Lighting

Lighting console

Roadhog 4,

Faderwing available in consultation



| i i cligged lixtures | | |
|-------------------------------|-----|--|
| 1 st FOH | 20x | Altman 2kW zoomprofile |
| | | |
| 2 nd FOH | 12x | ETC Source4 LED Tungsten HD 14° |
| Portal | 12x | Altman 1kW zoomprofile 12°-40° |
| | 8x | ADB C101 1kW PC |
| | | |
| Side bridges (per side) | 10x | Altman 2kW zoomprofile 12°-40° |
| | | |
| Proscenium (per side) | 3x | ETC Source4 LED Tungsten HD 15°- 30° |
| | | |
| Side of the portal (per side) | 6x | Altman 1kW zoomprofile 12°-40° |
| | | |
| Cyclorama | 14x | Robert Juliat Dalis 860 |
| | | |
| Follow spot | 2x | Robert Juliat Victor 1800W MSR |
| | | |
| House lights | | Led fixture, divided in 3 groups |
| | _ | |
| Curtain warmers | 4x | ADB C51 500W PC, from 1 st FOH |
| | _ | |
| Conductor lights | 2x | Altman 2kW zoomprofile, from proscenium (fixed position) |
| | | |
| Orientation lights | | Stage Left, Stage Right and upstage |

Extra fixtures

| extra fixtures | | |
|----------------|-----|---|
| Pars | 24x | ETC Source4 MultiPAR 750W; WFL, MFL, NSP, VNSP |
| | 6x | 6-bar ETC Source4 MultiPAR 750W; WFL, MFL, NSP, VNSP |
| | | |
| PC | 16x | ADB 1kW C103 met barndoors |
| | 16x | ADB 2kW C201 met barndoors |
| | | |
| Zoom profile | 16x | Altman 1kW zoomprofile 12°-40° |
| | | |
| Fresnell | 8x | Desisti 2kW Leonardo |
| | | |
| Flood | 8x | Floodlight |
| | | |



In consultation with other halls

| 12x | ETC Source4 LED Lustr+ 25°-50° |
|-----|--------------------------------|
| 12x | Showtec Pixelbar 18 Q4 |
| | |
| | |
| 8x | GLP Impression S350 profile |
| 8x | Clay Paky K10 B-Eye |
| 24x | Prolights Astra Wash 7Pix |
| | 12x 8x 8x |



Risers

| Risers | 40x | 200x100 cm | |
|-----------------|-----|------------------------------|--|
| NISEI S | 4UX | ZUUXIUU CIII | |
| | 2x | 100x100 cm | |
| | | | |
| Legs | 60x | 20 cm (15 risers) | |
| | 60x | 40 cm (15 risers) | |
| | 48x | 60 cm (12 risers) | |
| | 36x | 80 cm (9 risers) | |
| | 36x | 100 cm (9 risers) | |
| | | | |
| Stairs | 2x | 20, 40, 60 en 80 cm | |
| | | | |
| Masking | | 20, 40, 60, 80 en 100 cm | |
| | | | |
| Fall prevention | | Multiple lengths and amounts | |
| | | | |
| Fences | 14x | 95 cm high, 200 cm wide | |
| | 10x | 95 cm high, 100 cm wide | |



System

| Meyer Sound (controlled actively) | |
|-----------------------------------|---|
| Main | Meyer M'elody; auditorium fly bars stage left and right |
| | Meyer CQ1 en 600-HP; apron left and right |

Center

Meyer UPA; centre auditorium fly bar

Infill

Meyer UPM-2P; stage left and right Meyer UPM-2P; front fill on the

apron stage left and right

DSP Galileo 616 processor

Monitors

| Monitors | 4x | D&B MAX12 |
|------------|----|-------------------|
| | | |
| Amplifiers | 2x | D&B D6 Amplifiers |
| | | |

Multi-cable

| Analog | 36 ch. | Harting HAN108 audio FOH position auditorium |
|---------|--------|--|
| | | 36x XLR Stage left and right |
| | | 36x XLR in the control booth |
| | | |
| Digital | Cat7 | Ethernet Cat7 connection, assigned |

to D-rack

Consoles

| Digico | SD11 / SD9 | The use of our consoles is always in |
|--------|------------|--------------------------------------|
| | | consultation and depends on the |
| | | availability in our other halls. |
| | | |

D-rack Located on stage right

Extra material

Schouwburg Concertzaal Tilburg has, in addition to the standard systems in our halls, an extensive collection of consoles, mics, wireless transmitters, monitors and other supplies and cables. These can be used in consultation with our other halls. For information and availability reach out to our technical department, via technick@schouwburgconcertzaaltilburg.nl

Video

Schouwburg Concertzaal Tilburg has multiple audiovisual supplies, which contain beamers, laptops and mixing devices. Availability is always in consultation with our other halls. For information and availability reach out to our technical department, via techniek@schouwburgconcertzaaltilburg.nl





| Grand Piano | Steinway B | Serienr. 524797 | |
|---------------------------|-----------------|-------------------|--|
| | | | |
| Piano | Seiler | Serienr. 160630 | |
| The grand piano is always | available niano | only upon request | |



Dressing rooms

| Stage level | 5x | Ladies and men's toilets, connection for 3 washing machines and dryers, elevator to ground level |
|--------------|----|---|
| | | Dressing room 3 2-4 persons, adapted disabled toilet Dressing room 4,5 and 6 2-4 persons, shower, sink Dressing room 7 6-10 persons, sink |
| | | |
| Ground level | 3x | Ladies and men's toilets, 4 showers Dressing room 9 4-8 persons, sink Dressing room 10 12-25 persons, sinks Dressingroom 11 12-25 persons, sinks |

An audio feed of the auditorium and public address system are available from stage left and control booth.

Green room

Shared with the Studio.

Space for 50 persons, seating for 36 persons.

Analog tv feed, monitor with feed from the stage.

Small audio installation, mic available

An audio feed of the auditorium and public address system are available from stage left and control booth.

There is someone from our hospitality department available in the green room from the moment the artists arrive, until after intermission. Other times are in consultation with our hospitality department.

Information for catering or about the green groom:

- Carla Donkers, cdonkers@schouwburgconcertzaaltilburg.nl
 013 5490 308 (Corporate)
- Anne Rosenau, <u>arosenau@schouwburgconcertzaaltilburg.nl</u>
 013 5490 316 (impresario's)